# Transport Modelling to Inform Development Contribution Plan Apportionment

High Wycombe South

DCP

March 2022

Rev 1



kctt

## HISTORY AND STATUS OF THE DOCUMENT

Revision	Date issued	Reviewed by	Approved by	Date approved	Revision type
Rev A	02.08.2021	M Kleyweg	M Kleyweg	02.08.2021	Issued for Review
Rev B	08.11.2021	M Kleyweg	M Kleyweg	09.11.2021	Amended in Accordance with the Received Comments
Final	01.02.2022	M Kleyweg	M Kleyweg	01.02.2022	Amended in Accordance with the Received Comments
Rev 1	25.03.2022	M Kleyweg	M Kleyweg	25.03.2022	Amended to reflect progressed design

### DISTRIBUTION OF COPIES

Revision	Date of issue	Quantity	Issued to
Rev A	02.08.2021	1 (PDF)	
Rev B	09.11.2021	1 (PDF)	Ms Danielle Castaldini, Mr Peter Varellis (City of
Final	01.02.2022	1 (PDF)	Kalamunda) Mr Murray Casselton, Ms Benee Young (Element)
Rev 1	25.03.2022	1 (PDF)	in munay basseron, ins hence roung (Element)

Document Printed	25/03/2022 1:22 PM
File Name	C:\Users\jelena\Box\KCTT Projects\KC00000 Current Projects\KC00604.000 Forrestfield North - Structure Plan Preparation\Outgoing\DCP Transport Studies\Rev D\210927 Rev B Transport Modelling Report\KC00604 Transport Modelling Report DCP.docx
Author	Marina Kleyweg
Team Members	Jelena Simic / Ana Marijanovic/ Nemanja Marijanovic
Project Manager	Marina Kleyweg
Name of Project	High Wycombe South DCP
Name of the Document	High Wycombe South - Transport Modelling Report
Document Version	KC00604.000_R01_Rev 1

<b>a</b> ₹	Prepared by:	KCTT (Trading as KC Traffic and Transport Pty Ltd)
I Syst	ABN	35 148 970 727
Lified	Postal address:	PERTH: Unit 7, No 10 Whipple Street Balcatta WA 6021   BELGRADE: 23 Hilandarska, Beograd 11000
	Phone:	08 9441 2700
ISO 9001	Website:	www.kctt.com.au

Attachment 10.1.1.2

# Table of Contents

1 Executive Summary	5
2 Background	7
2.1 Background of the project	7
2.2 Purpose of Modelling and This Report	7
2.3 General Structure of This Report	7
2.4 Scope of Works and Literature	7
2.4.1 General Scope of Works	7
2.4.2 Additional Literature and Sources Used	8
2.4.3 Glossary of Abbreviations	8
3 Methodology of the Modelling	<b>9</b>
3.2 Methodology of Data Collation	9
3.3 Methodology of Traffic Modelling	9
3.4 Consultation With External Stakeholders	9
4 Input Analysis	10

4.1 Overview	
4.2 Existing Traffic on Network and Network Configuration	
4.2.1 Currently Available Traffic Count Data	
4.2.2 Existing Bus Routes	10
4.3 Traffic Generation / Attraction Rates	11
4.4 Anticipated Changes in High Wycombe South Project Area and Vicinity	12
4.4.1 High Wycombe South Project Area – Residential Land Use	
4.4.2 Non-Residential Land Use	
4.4.3 Traffic Generation / Attraction – Non-Residential Uses	
<ul> <li>4.4.3 Traffic Generation / Attraction – Non-Residential Uses</li></ul>	
<ul> <li>Findings of Network and Intersection Modelling</li> </ul>	15
<ul> <li>Findings of Network and Intersection Modelling</li></ul>	<b>15</b> 15
<ul> <li>Findings of Network and Intersection Modelling</li></ul>	<b>15</b> 15 17
<ul> <li>4.5 Regional Operational Model (ROM) and Metropolitan Land Ose Porecasting System MLOPS) Data</li> <li>5 Findings of Network and Intersection Modelling</li></ul>	
<ul> <li>4.3 Regional Operational Model (ROM) and Metropolitan Land Ose Porecasting System MLOPS) Data</li> <li>5 Findings of Network and Intersection Modelling</li></ul>	
<ul> <li>4.3 Regional Operational Model (ROM) and Metropolitan Land Ose Porecasting System MLOPS) Data</li> <li>5 Findings of Network and Intersection Modelling</li></ul>	
<ul> <li>4.3 Regional Operational Model (ROM) and Metropolitan Land Ose Porecasting System MLOPS) Data</li> <li>5 Findings of Network and Intersection Modelling</li></ul>	

# Tables

Table 1 – Status Liaison Activities (State Government Agencies)	9
Table 2 - Current Traffic Counts	10
Table 3 - Current public transport availability	10
Table 4 – Vehicular traffic generation / attraction rates per land use	11
Table 5 - Population and Dwelling Forecasts - High Wycombe South Project Area (source: element WA)	12
Table 6 - Estimated Rate of Build-Out (source: City of Kalamunda/Development WA)	12
Table 7 - Dwelling Forecasts – High Wycombe South Project Area (source: element WA)	12
Table 8 - Traffic Generation - Residential Land Use	12
Table 9 – Commercial Land Use in TOD Precinct (source: City of Kalamunda/Development WA)	12
Table 10 - Distribution of Non-Residential Land Uses Across TOD Development Cells	13

Table 11 - Retail Land Use - Traffic Attraction / Generation
Table 12 – Medical and Childcare Use Land Use - Traffic Attraction / Generation
Table 13 – High Wycombe Railway Station - Traffic Attraction / Generation
Table 14 - Commercial Use Land Use - Traffic Attraction / Generation
Table 15 – Community Land Use - Traffic Attraction/Generation
Table 16 – Primary School - Traffic Attraction / Generation
Table 17 - High Wycombe South Industrial Zone - Vehicular Traffic Attraction / Gene
Table 18 - Timing of Upgrades - Road Network
Table 19 - Timing of Upgrades - Intersections
Table 20 - Addressing SPP 3.6 Principles

	3
	3
1	3
1	3
1	4
1	4
ration 1	4
1	5
	7
1	9

PAGE

# Figures

Figure 1 - High Wycombe South Project Area Precincts (TOD and Residential) (source: element WA)
Figure 2 - Transport Modelling Methodology - Process Overview

Figure 3 - TOD Precinct Plan (source: element WA) ...... Figure 4 - Residential Precinct Plan (source: element WA).....

# Appendices

Appendix 1 – Methodology for Transport Modelling to Inform Development Contribution Plan Apportionment Analysis

Appendix 2 – Development Contribution Plan Modelling – Input Analysis Report

Appendix 3 – Transport Network Modelling to Inform Development Contribution Plan Apportionment Analysis

Appendix 4 – Intersection Modelling to Inform Development Contribution Plan Apportionment Analysis

#### Attachment 10.1.1.2

 	12
 	12

KC00604.000 High Wycombe South

## **1** Executive Summary

This report was prepared to summarise findings of a transport model for High Wycombe South Project Area comprising Residential Precinct and TOD Precinct. The transport model was prepared specifically to assist in preparation of Development Contribution Plan. Key road corridors and intersections were assessed. The costs are proposed to be distributed between the precincts in accordance with the transport impact made. Triggers for infrastructure upgrades were determined based on the preliminary assumption of Structure Plan build-out; however, practically they will depend on the uptake in particular areas of the structure plan. The table below summarises the upgrade requirements, land acquisition requirements and impact split per precinct. As discussed further in the report, if the precinct generates 10% or more of projected daily traffic on a road link or an intersection, contributions should be considered.

	Upgrades triggered in 2031								
Year	Infras	structure Element	BOQ	Current Configuration	Proposed Configuration	Land Acquisition Required	Residential Precinct %	TOD Precinct %	DCP Item
	R	Dundas Road (Maida Vale Road - Sorensen Road)	[RD8]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	15.25%	10.16%	Yes
	R	Dundas Road (Berkshire Road - Dundas Road Old)	[RD7]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	0.00%	2.00%	No
	R	Dundas Road (Berkshire Road - Harrison Road)	[RD6]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	7.73%	3.22%	No
	R	TOD Connector (Milner Road - Enterprise Boulevard)	[RD14]	The road doesn't exist at present	* Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	0.00%	60.82%	Yes
3	R	TOD Connector (Milner Road - Edge of TOD Precinct)	[RD15]	The road doesn't exist at present	* Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	69.40%	17.51%	Yes
20	R	TOD Connector (Edge of TOD Precinct – Roe Highway)	[RD16]	The road doesn't exist at present	* Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	100.00%	0.00%	Yes
	R	Raven Street (Milner Road - Brae Road)	[RD13]	The road doesn't exist at present	* Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	100.00%	0.00%	Yes
		M01 - Roe Highway / Maida Vale Road	[INT02]	Half - Interchange	Half - Interchange	No	18.85%	14.36%	Yes
		M15 - Dundas Road / Old Dundas Road (North)	[INT06]	T-intersection, full movement	Signalised Intersection	No	16.46%	7.85%	Yes
		M25 - Dundas Road / Dundas Road (South)*	[-]	T-intersection, full movement	T-intersection, full movement	No	0.00%	2.32%	No

### Notes 2031:

- Berkshire Road will trigger the requirement for upgrade to Integrator B carriageway in 2031; however, given that by 2041 it will require more substantial upgrade, it is assigned to a trigger year 2041.
- TOD Connector and Raven Street (south of Milner Road) don't exist at present. Although in 2031 both roads will carry traffic volumes appropriate for an Access Street, we have recommended the construction of the ultimate geometry to avoid unnecessary re-work and disruption to residents and businesses.
- The intersection Dundas Road / Dundas Road (South) does not require upgrading per se; however, the adjustment of the intersection is required once Dundas Road is upgraded.

	Upgrades triggered in 2041								
Year	'ear Infrastructure Element		Year Infrastructure Element BOQ Current Configuration Proposed Configuration		Proposed Configuration	Land Acquisition Required	Residential Precinct %	TOD Precinct %	DCP Item
	R	Berkshire Road (Roe Highway – Milner Road)	[RD1]	Two-way, one-lane undivided carriageway	Integrator A modified (two-way, two-lane divided carriageway)	Yes	15.96%	8.62%	Yes
	R	Maida Vale Road (Dundas Road - Raven Street)	[RD5]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	47.24%	11.88%	Yes
	R	Maida Vale (Raven Street - Milner Road)	[RD4]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	0.72%	24.06%	Yes
	R	Maida Vale (Milner Road – Roe Highway)	[RD3/3A]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	37.42%	17.25%	Yes
	R	Milner Road (Stewart Road - Maida Vale Road)	[RD10]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	52.67%	17.75%	Yes
	R	Milner Road (Sultana Road West - Stewart Road)	[RD2]	Two-way, one-lane undivided carriageway	Integrator B (two-way, one-lane divided carriageway)	Yes	54.17%	11.34%	Yes
	R	Milner Road (Berkshire Road - Sultana Road West)	[RD9]	Two-way, one-lane undivided carriageway	Integrator B modified (two-way, one-lane divided carriageway)	No	42.06%	14.81%	Yes
	R	Sultana Road West (TOD Connector – Milner Road)	[-]	Two-way, one-lane undivided carriageway	Two-way, one-lane undivided carriageway	No	0.00%	100.00%	Yes
	R	Sultana Road West (Milner Road – Edge of TOD Precinct)	[RD20]	Two-way, one-lane undivided carriageway	Two-way, one-lane undivided carriageway	No	57.75%	12.98%	Yes
	R	Sultana Road West (Edge of TOD Precinct – Cul-de-sac)	[RD20]	Two-way, one-lane undivided carriageway	Two-way, one-lane undivided carriageway	No	100.00%	0.00%	Yes
	R	Stewart Road (Milner Road - Brae Road)	[RD17]	Two-way, one-lane undivided carriageway	Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	100.0%	0.00%	Yes
	R	Raven Street (Maida Vale Road - Milner Road)	[RD12]	Two-way, one-lane undivided carriageway	Neighbourhood Connector A (two-way, one-lane divided carriageway)	Yes	64.83%	18.64%	Yes
	R	Enterprise Boulevard(TOD Connector – Maida Vale Road)*	[RD11]	Under construction.	Neighbourhood Connector A (two-way, one-lane divided carriageway)	No	0.00%	100.00%	Yes
	R	Brand Road(TOD Connector – Brae Road)**	[RD19]	Two-way, one-lane undivided carriageway	Two-way, one-lane undivided carriageway	No	100.00%	0.00%	Yes
	Ι	M02 - Maida Vale Road / Milner Road	[INT01]	T-intersection, full movement	Roundabout	Yes	33.35%	23.20%	Yes
	Ι	M03 - Milner Road / Stewart Road	[INT18]	T-intersection, full movement	Roundabout	Yes	64.72%	14.74%	Yes
4		M04 - Milner Road / Raven Street	[INT17]	T-intersection, full movement	Roundabout	Yes	61.43%	17.89%	Yes
21	I	M05 - Milner Road / TOD Connector	[INT05]	The intersection doesn't exist at present	Signalised Intersection	Yes	41.24%	16.36%	Yes

PAGE

KC00604.000 High Wycombe South

	Upgrades triggered in 2041								
Year	Year Infrastructure Element		BOQ	Q Current Configuration Proposed Configuration		Land Acquisition Required	Residential Precinct %	TOD Precinct %	DCP Item
		M06 - Milner Road / Berkshire Road /Dundas Road	[INT15]	T-intersection, full movement	Roundabout	Yes	17.23%	7.70%	Yes
		M07 - Berkshire Road / Roe Highway*	[-]	Interchange	Interchange	n/a	2.00%	1.20%	No
		M08 - TOD Connector / Brand Road	[INT16]	The intersection doesn't exist at present	Four-way, sign controlled	Yes	100.00%	0.00	Yes
		M09 - TOD Connector / Brae Road / Raven Street	[INT14]	The intersection doesn't exist at present	Four-way, sign controlled, full movement* (roundabout)	Yes	100.00%	0.00%	Yes
		M10 - Brae Road / Stewart Road	[INT09]	T-intersection, full movement	T-intersection, full movement	No	100.00%	0.00%	Yes
I M11 - Milner Road / Sultana Road West		[INT07]	Two staggered T-intersection, full movement	Intersection east of Milner Rd to be configured as Left In Left Out Right In	Vac	54.60%	11.53%	Yes	
					Sultana Rd West (west of Milner Rd) to be converted to Cul-De-Sac;	163	0.00%	100.00%	Yes
		M12 - Maida Vale Road / Dundas Road / Parking Access*	[INT14]	Roundabout	Roundabout	No	21.87%	8.75%	No
		M13 - Maida Vale Road / Enterprise Boulevard*	[INT12]	T-intersection, full movement	T-intersection, full movement	No	36.91%	17.55%	No
		M14 - Maida Vale Road / Raven Street	[INT13]	The intersection doesn't exist at present	T-intersection, full movement	Yes	37.82%	19.60%	Yes*
		M16 - Maida Vale Road / Newburn Road	[INT03]	T-intersection, full movement	Roundabout	Yes	37.72%	22.47%	Yes*
		M17 - Maida Vale Road / Butcher Road*	[-]	T-intersection, full movement	T-intersection, full movement	No	0.63%	20.91%	Yes*
		M18 - Maida Vale Road / Plover Road*	[-]	T-intersection, full movement	T-intersection, full movement	No	37.13%	26.04%	Yes*
	-	M19 - Maida Vale Road / Littlefield Road*	[-]	T-intersection, full movement	T-intersection, full movement	No	36.52%	25.62%	Yes*
		M20 - Milner Road / Nardine Close	[INT08]	T-intersection, full movement	Left in Left Out Right In	No	41.57%	11.73%	Yes*
		M21 - Berkshire Road / Bonser Road*	[-]	T-intersection, full movement	Left in Left Out	No	15.80%	8.50%	Yes*
		M22 - Berkshire Road / Ashby Close*	[-]	T-intersection, full movement	Left in Left Out	No	13.33%	8.10%	Yes*
		M23 - Berkshire Road / Walters Way*	[-]	T-intersection, full movement	Left in Left Out	No	14.78%	8.44%	Yes*
	I	M24 - Berkshire Road / Harrison Road*	[-]	T-intersection, full movement	Left in Left Out	No	13.65%	8.30%	Yes*

#### Notes 2041:

- Sections of Maida Vale Road may trigger Neighbourhood Connector A requirement by 2031; however, the upgrade is recommended by 2041. The cross-section was modified to minimise disturbance to the existing residences. Intersection along Maida Vale Road denoted with "\*" do not require an upgrade per se, however adjustments will be required to accommodate Maida Vale Road upgrade. The intersection Maida Vale Road / Dundas Road / Parking Access will not require an upgrade; however, adjustment will be required to accommodate upgrade of Maida Vale Road and Dundas Road.
- Similarly, sections of Milner Road may trigger Neighbourhood Connector A requirement by 2031; however, the upgrade is recommended by 2041 in its ultimate configuration Integrator B. Sections of Milner Road are modified Integrator B to minimise the impact on the existing operating businesses and Poison Gully Creek heritage area.
- Enterprise Boulevard will be constructed as a part of railway works, and no further major upgrades are likely to be required by the end of DCP lifespan. In 2041, Enterprise Boulevard is expected to reach the traffic warranting its configuration. • The Berkshire Road / Roe Highway interchange may require an upgrade as a result of growing passing traffic; however, the cost for upgrade cannot be apportioned to Residential nor TOD Precincts. Need and Nexus for the upgrade is established at 10%
- daily traffic contribution. Each of the Precincts contributes less than 10% to the total daily traffic at this intersection. As the traffic contribution is deemed insignificant, no portion of cost for upgrade can be attributed to either precinct. • The intersection TOD Connector / Brae Road / Raven Street was modelled as a four-way, sign controlled intersection as the traffic demand was fairly low and this configuration retained LOS A for the lifetime of the DCP. Subsequently, preliminary
- engineering design revealed this configuration cannot be implemented appropriately due to the existing road alignments, therefore the intersection is proposed to be configured as a roundabout. The percentage of traffic and therefore proportional costs remain the same.
- Berkshire Road is likely to require an upgrade to Integrator B in 2031; however, the upgrade is recommended in 2041 to a modified Integrator A configuration. The modification pertains to landtake required to facilitate two lane divided carriageway suitable for RAV vehicles. Intersections along Berkshire Road should be reconfigured as Left In Left Out and will not require land to be acquired in addition to the requirement associated with the road widening.
- Brand Road will require an upgrade at the time when primary school is constructed.

	Upgrades triggered in 2050									
Year	Infrastructure Element	BOQ	Current Configuration	Proposed Configuration	Land Acquisition Required	Residential Precinct %	TOD Precinct %	DCP Item		
2050	R Brae Road (TOD Connector – Roe Highway)	R18	Two-way, one-lane undivided carriageway	Neighbourhood Connector B (Two-way, one-lane undivided carriageway)	No	100.00%	0.00%	Yes		

#### Notes 2050:

Brae Road is expected to reach the traffic volume warranting Neighbourhood Connector B configuration in 2050. Practically, it is likely that Brae Road will be progressively upgraded as adjacent land is developed.

PAGE

## 2 Background

#### 2.1 Background of the project

The High Wycombe South Project Area (formerly known as Forrestfield North) is within the City of Kalamunda, near the underconstruction High Wycombe Railway Station, which is likely to open by mid-2022. West Australian Planning Commission (WAPC) approved District Structure Plan (DSP) for High Wycombe South Project Area on 29 September 2016.



#### Figure 1 - High Wycombe South Project Area Precincts (TOD and Residential) (source: element WA)

This area includes two major precincts with separate structure plans – Residential Precinct Local Structure Plan (LSP) and Transit-Oriented Development (TOD) Precinct Activity Centre Structure Plan (ACSP). While the Residential Precinct will feature a Primary School, District Open Space, and various residential dwellings, the TOD Precinct will likely feature a mix of commercial and residential uses and a community hub following detailed planning by Development WA. Given that the DSP area is over 200ha, the traffic impact on the surrounding network will be exceptionally high.

The High Wycombe South Residential Precinct LSP was endorsed by WAPC on 27 July 2020. In collaboration with Development WA, the City of Kalamunda and their consultant team are currently preparing the High Wycombe South ACSP. An amendment to the High Wycombe South Residential Precinct Local Structure Plan is being progressed by the City of Kalamunda and is currently being advertised for public comment. The DCP has been prepared to reflect the proposed amendments in the draft LSP.

#### 2.2 Purpose of Modelling and This Report

As major infrastructure upgrades are required to cater for developments of this scale, a robust traffic model must be prepared to assess road network requirements adequately. While KCTT has prepared transport modelling for the Residential Precinct and the District Structure Plan in the past, the purpose of this model is first and foremost to quantify and apportion the impact on the existing network, determine the extent of required upgrades, and allow for the preparation of the Development Contribution Plan.

Modelling prepared for High Wycombe South Residential Precinct LSP focused on the maximum possible build-out. However, to appropriately assess development demand and estimate required infrastructure, modelling for Development Contribution Plan focuses on the most realistic outcome. This model builds on models developed throughout the project, and therefore network and intersection modelling are developed in microsimulation packages.

Modelling is prepared for 2031 (15% of the development completed), 2041 (65% of development completed) and 2050+ (100% of development completed) horizon years. Further to this, the network model was finetuned and developed down to the individual cell level to assess the impact on all internal roads.

This report will outline network and intersection modelling findings and the apportionment of impact for each precinct on each infrastructure element.

#### 2.3 General Structure of This Report

This report will have five (5) main sections.

Section 1 – Background – provides a brief overview of the past activity on this project and the purpose of this modelling and reporting exercise.

Section 2 – Methodology of the Modelling – summarises approaches and methods for data collection and preparation of network and intersection models, as documented in Appendix 1 of this report.

Section 3 – Input Analysis – Outlines key information used for modelling. Appendix 2 of this report provides full documentation on the consideration and selection of data for modelling.

Section 4 – Findings of Network and Intersection Modelling – provides an overview of the anticipated development impact on the infrastructure. A very condensed section provides basic upgrade requirements, estimated timeframe for the upgrade, and land acquisition impact.

Section 5 – Impact on the Cost Apportionment – discusses elements of the SPP 3.6 applicable to this process. Further on, this section provides a summary of each precinct's impact on each road and intersection. Spatial plans are also provided to enable easier correlation of the proposed upgrades and location of the infrastructure elements.

#### 2.4 Scope of Works and Literature

#### 2.4.1 General Scope of Works

The scope of works for this project was defined in a document titled "*Scope of Works: Forrestfield North Development Contribution Plan (DCP) – Work Required to Prepare DCP*, prepared by the City of Kalamunda in July 2020. Development WA reviewed this document, and the scope of works was endorsed as outlined below.

#### KC00604.000 High Wycombe South

- 1. Traffic Modelling and Needs Assessment:
  - a. Traffic modelling to be undertaken to determine assumptions for the traffic distribution of the following: i. Background traffic (e.g. existing traffic)

ii. Development generated traffic (Traffic that has been generated from the High Wycombe South development) - Future population and development projections to determine development generated traffic.

iii. Traffic generated by attractors to the Precinct (e.g. train station, school).

b. Based on the outcomes from the modelling, allocate percentages of the three categories listed above to the TOD Precinct. Residential Precinct and outside the DCA. These percentages are to inform apportionment of costings for the DCP.

#### 2. Community Infrastructure Needs Assessment:

a. Determine apportionment of community infrastructure between TOD Precinct, Residential Precinct and outside High Wycombe South (it is noted that some of this work has been done as part of the preparation of the LSPs). Population, development projections and catchments of community infrastructure to inform apportionment.

#### Infrastructure Concepts: 3.

- a. Prepare updated concepts for all roads as per Residential precinct LSP and latest TOD precinct ACSP.
- b. Prepare concepts for all drainage areas as per Residential precinct LSP and latest TOD precinct ACSP.
- c. Prepare concepts for all POS as per Residential precinct LSP and latest TOD precinct ACSP.
- d. Prepare concepts for all community infrastructure items as per Residential precinct LSP and latest TOD precinct ACSP. (It is noted that same of this work has been done.)

#### Note:

#### Drainage:

Assumptions will need to be made in relation to concept plans for the drainage areas in the TOD precinct based on the best information currently available. These assumptions will need to be reviewed once further information in relation to environmental and drainage investigations are made available through the investigations being undertaken by DevelopmentWA. Community infrastructure:

Assumptions will need to be made in relation to concept plans for community infrastructure in the TOD precinct based on the best information currently available. These assumptions will need to be reviewed once further information is made available through the investigations being undertaken by METRONET.

#### 4. Cost estimates:

- a. Prepare cost estimates for all roads as per updated concepts
- b. Prepare cost estimates for drainage as per updated concepts.
- c. Prepare cost estimates for POS as per updated concepts.
- d. Prepare cost estimates for community infrastructure as per updated concepts. (It is noted that some of this work has been done. Community Hub Project for the TOD Precinct to help inform this item).
- e. Cost estimates for 2 year maintenance period of POS to be included.
- f. Cost estimates relating to works required to be undertaken as part of the Strategic Conservation Management Plan and reasonably included in a DCP (POS Management Plan, demolition of buildings etc.)
- g. Land acquisition requirements and cost estimates.

#### 5. Technical Report

Prepare a report which collates the technical information generated from the above, plus any relevant information already prepared. Report to address the following:

- 1. How the technical information prepared addresses the provisions of State Planning Policy 3.6.
- 2. Establish the identification and justification of need and nexus where the relationship between the need for infrastructure and the new development is clearly established.
- 3. Determine apportionment of infrastructure costs to the Residential Precinct, TOD Precinct and outside the DCA.
- 4 Establish projected rate of development to help inform a project plan to determine timing of funds being received and infrastructure being delivered.

Methodology discussed in this report pertains to deliverable No 1 (Traffic Modelling and Needs Assessment). The findings of deliverable No 1 will be directly fed to deliverables No 3 and No4.

#### 2.4.2 Additional Literature and Sources Used

#### **Documents:**

- Forrestfield North District Structure Plan
- Forrestfield North Residential Precinct Structure Plan, July 2020
- Transport Impact Assessment Guidelines (set), WAPC 2016 •
- Operational Modelling Guidelines, MRWA 2021 •
- Transport Modelling Guidelines for Activity Centre Structure Plans, DoT 2016 •
- Australian Transport Assessment and Planning Guidelines, ATAP 2016
- NSW RTA Guidelines to Traffic Generating Developments, NSW RTA 2002 (updated in 2013)
- · Forrestfield North Development Contribution Plan Yield Analysis, Surrounding Development Projections, City of Kalamunda, April 2021
- Forrestfield Station Multi-Storey Car Park, Traffic Impact Assessment, Aurecon (PTA), September 2019
- ROM24 Model Plots provided by MRWA in December 2020 and in 2016 for purposes of DSP modelling
- ROM24 Model Link volume plots provided by MRWA in July 2021
- MLUFS population projections, provided to KCTT in December 2020
- High Wycombe Station Precinct Retail & Commercial Assessment, Urbis (development WA), April 2021
- High Wycombe Station Access Strategy, GHD (PTA), April 2021
- State Planning Policy 3.6 Infrastructure Contributions, WAPC, April 2021

#### Sources

- City of Kalamunda Community ID
- Australian Bureau of Statistics
- Main Roads WA Portal

#### 2.4.3 Glossary of Abbreviations

- AADT (Average Annual Daily Traffic)
- Precinct Activity Centre Structure Plan (ACSP)
- AS (Access Street Liveable Neighbourhoods)
- DOS (District Open Space) •
- DoT (Department of Transport) •
- DPLH (Department of Planning, Lands and Heritage)
- DSP (District Structure Plan) •
- FFN (Forrestfield North)
- GEH (Goodness of fit measure)
- HWS (High Wycombe South)
- IA (Integrator A Liveable Neighbourhoods)
- IB (Integrator B Liveable Neighbourhoods)
- LSP (Local Structure Plan)
- MLUFS (Metropolitan Land Use Forecasting System)
- MRWA (Main Roads Western Australia) •
- NCA / NCB (Neighbourhood Connector A /B Liveable Neighbourhoods)
- OMG (Operational Modelling Guidelines)
- PTA (Public Transportation Authority)
- ROM24 (Regional Operational Model)
- TOD (Transit Oriented Development) •
- STEM (Strategic Transport Evaluation Model) •
- VPD (Vehicles Per Dav)
- VPH (Vehicles Per Hour)

PAGE

KC00604.000 High Wycombe South

## **3** Methodology of the Modelling

#### 3.1 Overview

KCTT prepared a document "*Methodology for Transport Modelling to Inform Development Contribution Plan Apportionment Analysis*" in February 2021 for the City of Kalamunda and the stakeholder group outlining the process and the sequence of all actions related to the transport modelling. This document is provided as in Appendix 1 of this report.



#### Figure 2 - Transport Modelling Methodology - Process Overview

This document was peer-reviewed by an independent entity. The City of Kalamunda endorsed the subsequent revision of the report.

## 3.2 Methodology of Data Collation

Data intended to be used as input are collated from various sources. Main Roads Western Australia (MRWA) have provided Regional Operational Model (ROM) plots for various horizon years showing forecasted traffic for main transport routes.

This was supplemented by projections of dwelling yields from the Metropolitan Land Use Forecasting System (MLUFS).

Current traffic counts were obtained (where available) from the City of Kalamunda for local roads and from the MRWA traffic map and traffic portal for State infrastructure. Current road classification and speed limits were obtained from the MRWA portal, while various population data were obtained from the City of Kalamunda's Community ID website.

Current intersection and road configuration were obtained from aerial imagery supplied by Nearmaps.

#### 3.3 Methodology of Traffic Modelling

Network models were prepared in Q-Paramics as this is the software used for modelling High Wycombe South since District Structure Plan preparation. Intersection modelling was completed in SIDRA Intersection software.

Models were generally prepared in accordance with Operational Modelling Guidelines, prepared by MRWA. Where guidelines could not be followed, MRWA were informed, and instruction was received on how to proceed.

## 3.4 Consultation With External Stakeholders

KCTT contacted various State authorities to confirm basic assumptions and methodology on essential modelling items in establishing methodology. The status of responses is provided in the table below:

#### Table 1 – Status Liaison Activities (State Government Agencies)

	Traffic Generation Rates	Transport Mode Share	ROM Model Calibration	Model Validation
Main Roads WA				
Department of Planning, Lands and Heritage				
Public Transport Authority				
Department of Transport				
Legend:				

 
 Authority has no comment / information
 Authority not contacted as it has no jurisdiction
 Authority provided appropriate comments

Department of Planning, Lands and Heritage (DPLH) and Public Transportation Authority (PTA) confirmed they have no comment to make on assumptions they were presented with.

KC00604.000 High Wycombe South

## 4 Input Analysis

#### 4.1 Overview

Given the scope of the model, input for modelling was analysed in a separate technical report. The Input Analysis Report is provided as an appendix of this report. This section will outline only the most important parameters used in the modelling. For further detail please refer to Appendix 2 of this report.

#### 4.2 Existing Traffic on Network and Network Configuration

Data on the existing traffic on the network was collated via Main Roads WA and the City of Kalamunda, inclusive of current daily volumes, peak volumes, the composition of vehicles on the network (Austroads classification). In addition to this, data was collected on road hierarchy, speed limit, RAV networks and general network configuration.

There is no meaningful data on pedestrian and cycling traffic; however, given that the existing infrastructure is poorly developed at present, minimal activity is anticipated.

Data on bus traffic was collated from PTA schedules and referenced against other data collected.

#### 4.2.1 Currently Available Traffic Count Data

The table below outlines currently available traffic count data on key roads within and in the vicinity of the High Wycombe South Project Area.

Table 2 - Current Traffic Counts								
Road	Location	VPD	Heavy Vehicles	Year	Source			
	North of Berkshire Road	43,557	16.6%	2016	MRWA			
Roe Highway	South of Berkshire Road	58,806	15.5%	2018	MRWA			
	North of Maida Vale Road	44,657	12.7%	2019	MRWA			
	South of Raven Street	1,537	9.2%	2018	City of Kalamunda			
Milnor Pood	Northeast from Stewart Road	1,807	9.4%	2018	City of Kalamunda			
Millier hoau	Southwest of Sultana Road West	2,397	14.1%	2018	City of Kalamunda			
	South of Eureka Street	3,864	19.3%	2019	City of Kalamunda			
	East from Milner Road	3,711	8.0%	2018	City of Kalamunda			
Maida Valo Road	West from Milner Road	3,062	7.3%	2018	City of Kalamunda			
malua vale nuau	East of Dundas Road	2,430	7.0%	2018	City of Kalamunda			
	West of Butcher Road	1,994	9.1%	2019	City of Kalamunda			

Road	Location	VPD	Heavy Vehicles	Year	Source
Maida Vala Daad	East of Plover Road	8,851	7.6%	2019	City of Kalamunda
Malda vale koad	West of Jaeger Court	3,870	8.3	2020	City of Kalamunda
	South of Maida Vale Road	4,770	19.4%	2017	MRWA
	North of Maida Vale Road	5,697	12.3%	2018	City of Kalamunda
Dundas Road	North of Berkshire Road	4,267	19.4%	2018	City of Kalamunda
	South of Kapok Court	5,953	11.5%	2020	City of Kalamunda
	North of Daddow Road	3,794	36.7%	2020	MRWA
	West of Roe Highway	4,199	23.0%	2016	MRWA
Berkshire Road	West of Roe Highway	6,531	26%	2020	MRWA
	East of Milner Road	5,054	15.9%	2016	City of Kalamunda

Most roads in the vicinity of High Wycombe South Project Area have a high percentage of heavy vehicles. This is not surprising given the industrial land use near the subject area.

#### 4.2.2 Existing Bus Routes

The table below outlines currently available bus routes in the vicinity of the High Wycombe South Project Area. Lack of connection and inaccessibility are the main reasons that High Wycombe South Project Area residents are not using public transportation services.

#### Table 3 - Current public transport availability

Route	Road	Peak frequency	Approximate daily (workday) number of vehicles per direction
294	Maida Vale Road	40 minutes	28
296	Maida Vale Road	15 minutes	15
298	Maida Vale Road	30 minutes	3

It is anticipated that bus feeder routes will be introduced, enhancing the availability of public transport for residents.

KC00604.000 High Wycombe South

### 4.3 Traffic Generation / Attraction Rates

There is a limited source of West Australian based traffic generation rates. We have used rates from WAPC Transport Assessment Guidelines for Developments where applicable. Unavailable rates were supplemented by the rates provided in the NSW RTA Guide to Traffic Generating Developments as the most relevant, Australian based reference document. Rates that were not available in either of these documents were referenced from ITE Trip Generation Rates Handbook. Some of the traffic generation rates were adjusted to suit local conditions. Where these adjustments were applied, an explanation was provided. In many instances, the WAPC Guidelines Volume 5 (Technical Handbook) offers an hourly traffic generation rate without a daily traffic generation rate. In those instances, daily rates were sourced from the other two reference documents.

Land Use	Value (vehicular trips per unit)	Period	Split (In / Out)	Source	Note
Residential –	10 / dwelling	daily	50/50		
and less)	0.8 / dwelling	AM / PM peak	AM 25/75 PM 67/33	WAPC TAGD	
Residential Medium density	8 / dwelling	daily	50/50	NSW RTA GTGD	
(R30-R40)	0.8 / dwelling	AM / PM peak	AM 25/75 PM 67/33	WAPC TAGD	
Residential	6.5 / dwelling	daily	50/50	NSW RTA GTGD	
(R50-R60)	0.65 / dwelling	AM / PM peak	AM 25/75 PM 67/33	WAPC TAGD	
Residential High	5.5 / dwelling	daily	50/50	NSW RTA GTGD	
Density (R80)	0.55 / dwelling	AM / PM peak	AM 25/75 PM 67/33	WAPC TAGD	
Residential High	5 / dwelling	daily	50/50	NSW RTA GTGD	
and more)	0.5 / dwelling	AM / PM peak	AM 25/75 PM 67/33	WAPC TAGD	
01	121/100m2	Daily	50/50		
Snopping	AM – 2.5/100m <sup>2</sup> PM – 10/100m <sup>2</sup>	AM / PM peak	AM 80/20 PM 50/50	NSW RIA GIGD	
Showroom	17/100m <sup>2</sup>	Daily	50/50		
Shopping	2.7/100m <sup>2</sup>	AM / PM peak	PM 50/50	NSW KI	

Land Use	Value (vehicular trips per unit)	Period	Split (In / Out)	Source	Note	
Primary School	2 / person	daily	50/50	Derived from hour nature o	y peak rate and the f the use	
	1/ person	AM / PM peak	50/50	WAPC TAGD		
Childeare Centre	4 / child + 1/employee	Daily	50/50	Derived fror	n experience	
	0.8 / child 0.7 / child	AM / PM peak	50/50	Adjusted rate from	n NSW RTA GTGD	
Office and	10 / 100m² GFA	daily	50/50	NSW RTA GTGD		
Commercial	2 / 100m² GFA	AM / PM peak	AM 80/20 PM 20/80	WAPC TAGD		
Warahawaa	4 / 100m²GFA	daily	50/50			
warenouse	0.5 / 100m <sup>2</sup> GFA	AM / PM peak	AM 80/20 PM 20/80	NSW KIA GIGD		
Footowi	5 / 100m² GFA	daily	50/50			
Factory	1 / 100m² GFA	AM / PM peak	AM 80/20 PM 20/80			
l inte Induction	4.6 / 100m² GFA	daily	50/50	This rate was derived as an average of		
Light industry	0.7 / 100m <sup>2</sup> GFA	AM / PM peak	AM 80/20 PM 20/80	Warehouse and Factory Rates		
District Open Space	71.33 / playing field	Daily	50/50	ITE CTGR		
Acustic Facility	1.5 / person	Daily	50/50	This rate was de	erived as per the	
	0.15 / person	AM/PM peak	AM 70/30 PM 30/70	description	on below.	
Railway Station	4,000	Daily	50/50	PTA Transport Assessment for		
– Kiss and Ride	1,000 (ultra-peak hour)	AM/PM peak	50/50	High Wycombe Station		
Railway Station – Public parking	2 / bay	Daily	50/50	This rate was der nature of parkin parking) and und that peak hour dist kiss and dro	ived based on the g (all day transit er the assumption ribution will be like p off facility	

kiss and drop off facility

KC00604.000 High Wycombe South

#### 4.4 Anticipated Changes in High Wycombe South Project Area and Vicinity

High Wycombe South Project Area comprises two distinct areas whose development will be guided by separate structure plans: Residential Precinct and Transit-Oriented Development (TOD) precinct. At present, Residential Precinct features larger residential lots intended for rural residential use. At the same time, the TOD precinct has been a worksite for the construction of the High Wycombe Railway Station.

Given that the latest Census (2016) recorded 313 dwellings in the High Wycombe South Project Area, by 2050 population will increase significantly as per the schedule below:

Table 5 - Population and Dwelling Forecasts - High Wycombe South Project Area (source: element WA)									
		Year 2031	Year 2041	Year 2050+					
TOD Provinct	Dwellings	69	508	508					
TOD Freemet	Population	151	1,359	1,359					
Desidential President	Dwellings	340	1,594	2,417					
Residential Precinct	Population	850	3,948	5,998					

Many different factors will dictate the rate of development in the coming years. For purposes of modelling, the following rates were assumed:

#### Table 6 - Estimated Rate of Build-Out (source: City of Kalamunda/Development WA)

	2031	2041	2050+
Rate of Buildout	15%	65%	100%

The rate of development may vary over the development cells depending on the interest. For purposes of this report, a uniform build-out is assumed across all cells.

#### 4.4.1 High Wycombe South Project Area – Residential Land Use

The residential Precinct of the High Wycombe South Project Area will be developed over seven (7) development cells. Transit-Oriented Development (TOD) Precinct will be developed over six (6) development cells; however, residential land use will feature only in two (2) cells.

The anticipated number of dwellings for each cell is shown in the table below:

#### Table 7 - Dwelling Forecasts - High Wycombe South Project Area (source: element WA)

		<u>, , , , , , , , , , , , , , , , , , , </u>	
Residentia	al Precinct	TOD P	recinct
Cell Number	No Dwellings	Cell Number	No Dwellings
1	55	1A	0
2	44	1B	301
3	261	10	0
4	226	1D	0
5	352	1E	0
6&7	842		207
8	637		
Total	2,417	Total	508





Figure 3 - TOD Precinct Plan (source: element WA)

Following traffic generation was developed for the residential component.

#### Table 8 - Traffic Generation - Residential Land Use

	20	31	20	41	2050+		
Zone	Daily Traffic (VPD)	Peak Traffic (VPH)	Daily Traffic (VPD)	Peak Traffic (VPH)	Daily Traffic (VPD)	Peak Traffic (VPH)	
9 (Cell 1)	66	7	288	29	440	44	
10 (Cell 2)	53	5	232	23	352	35	
11 (Cell 3)	313	31	1,360	136	2,088	209	
12 (Cell 4)	270	27	1,168	117	1,800	180	
13 (Cell 5)	422	42	1,832	183	2,816	282	
14 (Cell 6)	774	77	3,353	335	5,158	516	
15 (Cell 7)	606	61	2,625	263	4,039	404	
16 (TOD Residential)	171	17	1,139	74	1,139	114	
18 (1B HWS station)	226 23		1,505	98	1,505	151	
	2,900 290		13,502	1,257	19,336	1,934	

#### 4.4.2 Non-Residential Land Use

Besides residential land use, High Wycombe South Project Area will feature a number of non-residential uses. TOD Precinct will have a number of non-residential land uses to support new transit node. Current estimates are as follows:

Table 9 – Commercial Land Use in TOD Precinct (source: City of Kalamunda/Development WA)										
Year	2030	2040	2050							
Retail		5,160 m <sup>2</sup> (152)	5,160 m <sup>2</sup> (152)							
Commercial	1,100 m² (32)	450 m² (18)	1,200 m² (48)							
Medical		450 m² (5)	1,200 m <sup>2</sup> (14)							
Childcare	400 m <sup>2</sup> (12)	1,250 m² (36)	1,250 m <sup>2</sup> (36)							
Showroom Retail	-	2,500 m <sup>2</sup> (32)	2,500 m <sup>2</sup> (32)							
Total	1,500 m <sup>2</sup> (44)	9,810 m <sup>2</sup> (243)	11,310 m² (282)							
IOTAI	1,500 m² (44)	9,810 m²(243)	11,310 M² (282)							



Figure 4 - Residential Precinct Plan (source: element WA)

PAGE

KC00604.000 High Wycombe South

As we weren't provided with the breakdown per development cell, the following breakdown was assumed:

#### Table 10 - Distribution of Non-Residential Land Uses Across TOD Development Cells

Cell Number	Food Retail	Non-Food Showroom Retail Retail		Medical	Childcare	Commercial
1A	0	0	100%	0	0	0
1B	100%	50%	0	100%	70%	0
10	0	0	0	0	0	0
1D	0	0	0	0	0	0
1E	0	50%	0	0	0	100%
2	0	0	0	0	30%	0

For purposes of this report, it was assumed that the nominated Retail floor space would comprise 70% "Food Retail" and 30% of "Non-food Retail". It was assumed that the Showroom Retail would be predominantly situated in Cell 1A, gradually replacing light industry activities. The majority of other non-residential land uses will be situated in Cell 1B, abutting main internal transit corridors. Cell 2 is expected to be a predominantly residential cell.

Community facilities in TOD Precinct may feature an aquatic centre with two areas (indoor and outdoor), a water-play recreational area and a gym if constructed at this scale. If constructed at the aforementioned scale, the community facility is anticipated to attract approximately 450,000 visitors per annum when fully established.

The Residential Precinct will feature a District Open Space and a Primary School.

#### 4.4.3 Traffic Generation / Attraction – Non-Residential Uses

Retail land use is expected to start developing in 2031 and be fully developed by 2041. While no further development is expected for retail land use between 2041 and 2050, the population in the area is expected to grow significantly, and therefore the proportion of internal trips will increase.

The table below focuses on the PM peak as the higher peak. For a full detailed analysis, please see Network Modelling Report.

		20	31		2041				2050+			
Zone	Total VPD	Total PM VPH	External VPD	External PM VPH	Total VPD	Total PM VPH	External VPD	External PM VPH	Total VPD	Total PM VPH	External VPD	External PM VPH
17 (1a)	0	0	0	0	500	100	425	85	500	100	400	80
18 (1b)	551	46	385	32	4,371	361	2,841	235	4,371	361	2,404	199
19 (1c)	0	0	0	0	0	0	0	0	0	0	0	0
20 (1d)	0	0	0	0	0	0	0	0	0	0	0	0
21 (1e)	39	0	35	8	310	100	263	62	310	100	248	62
Total	590	46	420	40	5,181	561	3,529	382	5,181	561	3,052	341

#### Table 11 - Retail Land Use - Traffic Attraction / Generation

Childcare and Medical land uses are expected to increase in the period 2031-2050 iteratively; however, the percentage of external trips is expected to be higher than the percentage of internal trips on a daily basis throughout the period.

### Table 12 - Medical and Childcare Use Land Use - Traffic Attraction / Generation



High Wycombe Railway Station is expected to be opened in mid 2022. For modelling purposes, it is assumed that it will reach its full capacity when it comes to vehicular attraction by 2041. While the patronage is expected to grow to 2050, the growth in the High Wycombe South Project Area population will increase the percentage of walking and cycling arrivals.

#### Table 13 - High Wycombe Railway Station - Traffic Attraction / Generation



Commercial land use is expected to be fully developed in 2050, and throughout the study period, it is anticipated that vehicular traffic attracted to this land use will be mostly external.

#### Table 14 - Commercial Use Land Use - Traffic Attraction / Generation

		20	41		2050+				
Zone	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	
21 (1E)	45	9	43	9	120	24	114	23	

Should the community site be constructed at the envisioned scale, the facility is not expected to become operational before 2041 and is not likely to reach operational peak immediately. The facility is expected become operational by 2041; however, it is not likely to reach an operational peak immediately.

KC00604.000 High Wycombe South

#### Table 15 - Community Land Use - Traffic Attraction/Generation

		20	41		2050+				
Zone	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	
18 (1B)	942	94	754	75	1884	188	1507	150	

Primary School is expected to open by 2041; however, it will reach its full capacity by 2050. Most of the trips associated with this land use will be internal to the project area.

#### Table 16 - Primary School - Traffic Attraction / Generation

		20	41		2050+				
Zone	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	TOTAL VPD	TOTAL VPH	External VPD	External AM VPH	
22 (Primary School)	600	300	120	60	1080	540	216	108	

High Wycombe South Industrial Zone is expected to be fully operational by 2031.

#### Table 17 - High Wycombe South Industrial Zone - Vehicular Traffic Attraction / Generation

Zone	Total Area (m²)	Equivalent Area (m²)	VPD	VPH
23	241,366	48,273	2,414	483
24	154,967	30,993	1,550	310
25	174,543	34,909	1,745	349
26	83,945	16,789	839	168
	654,821	130,964	6,548	1,310

As the City of Kalamunda is looking to meet its projected population targets and associated physical and social infrastructure requirements, changes in the vicinity of the High Wycombe South Project Area are inevitable. These were reviewed, and the impact on the subject area was assessed.

## 4.5 Regional Operational Model (ROM) and Metropolitan Land Use Forecasting System MLUFS) Data

In December 2020, KCTT received the following ROM plots from MRWA:

- 41696\_LVP\_All Day\_Y16 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y16 Forrestfield DCP\_TUE
- 41696\_LVP\_All Day\_Y21 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y21 Forrestfield DCP\_TUE
- 41696\_LVP\_All Day\_Y26 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y31 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y36 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y36 Forrestfield DCP\_TUE
- 41696\_LVP\_All Day\_Y41 Forrestfield DCP\_MLUFS140
- 41696\_LVP\_All Day\_Y41 Forrestfield DCP\_TUE
- 41696\_Validation\_Y16 Forrestfield DCP\_MLUFS140
- 41696\_Validation\_Y16 Forrestfield DCP\_TUE
- 41696\_ZBP\_Forrestfield DCP\_MLUFS140 (schedule of zones)
- 41696\_ZBP\_Forrestfield DCP\_TUE (schedule of zones)

KCTT have been supplied with two distinct sets of ROM plots based on different population scenarios.

One set is based on the MLUFS land-use model and hereon will be referred to as "ROM Scenario 1". The other scenario was prepared to examine the impact of the Tonkin Highway extension and hereon will be referred to as "ROM Scenario 2". ROM Scenario 2 also shows slight variations in population assumptions to ROM Scenario 1.

The map of zones for each scenario was used to correlate existing statistical data and the number of dwellings to determine the population growth anticipated by the State Government.

KCTT received population scenarios for the 2041 horizon year only as a part of this package.

In-network modelling, KCTT relied predominantly on the "ROM Scenario 1".

In July 2021, KCTT received additional link volume plots for sections of Dundas Road and Berkshire Road. We only received link plots for 2041. These plots were used to derive passing traffic on Dundas Road and Berkshire Road.

PAGE

KC00604.000 High Wycombe South

## 5 Findings of Network and Intersection Modelling

## 5.1 Network Configuration

The table below outlines the requirement for upgrades on each section of the network. The table shows anticipated vehicles per day (VPD) on the link, Liveable Neighbourhoods classification (LN), applicable road reservation width required (RR) and whether the land acquisition is necessary. The current size of the road reservation was sourced from Nearmap in June 2021. The critical information in the table below is when the upgrade of a particular link is required and whether this upgrade requires additional land acquisition. Details of modelling, conclusions and apportionment are provided in Appendix 3 of this report.

Liveable Neighbourhoods classify streets based on the function and volume of vehicular traffic. This classification is generally used as a reference for planning purposes. Once the road is constructed and functional, the Liveable Neighbourhoods classification is replaced by the Main Road WA classification. However, for comparison purposes, the table below will outline Liveable Neighbourhoods equivalent road class on existing roads, based on the current traffic counts.

The reference in the brackets pertains to the infrastructure element in the associated Bill of Quantities.

Boad				LN		2	031				2041				2050	
Road	BOQ	Section	RR Current	category Current	VPD	LN	RR	Land Acquisition	VPD	LN	RR	Land Acquisition	VPD	LN	RR	Land Acquisition
	[RD1]	W of Roe Hwy	20m	NCA	16,500		25.2m (20m)	No	21,900		35.6m*(25m)	Yes	25,843		35.6m*(25m)	No
Berkshire Road	[-]	E of Roe Hwy	20m	NCA	17,900	IB	25.2m (20m)	No	25,600	IA	35.6m	Yes	31,805	IA	35.6m	No
	[RD1]	S of Milner Rd	30m	NCA	15,700	-	25.2m (20m)	No	21,000		35.6m*(25m)	Yes	24,915		35.6m*(25m)	No
	[RD6]	S of Berkshire Rd	Varies	NCA	11,100		25.2m (20m)	No	13,400		25.2m (20m)	No	15,200	חו	25.2m (20m)	No
Dundas Road	[RD7]	SW of Old Dundas Rd	Varies	NCA	10,500	IB	25.2m (20m)	No	11,700	IB	25.2m (20m)	No	13,700	IB	25.2m (20m)	No
	[RD8]	N of Old Dundas Rd	Varies	NCA	12,500	_	25.2m (20m)	No	16,600		25.2m (20m)	No	20,000	IA (IB)	25.2m (20m)	No
	[RD5]	E of Enterprise Blvd	25m	AS/NCB	3,400	NCA	24.4m (20m)	No	6,200	NCA	25.2m (20m)	No	7,700	IB	25.2m (20m)	No
Maida Vale Road	[RD4]	E of Raven St	20m	AS/NCB	2,900	NCB	19.4m	No	4,300	NCA	24.4m (20m)	No	4,500	NCA	24.4m (20m)	No
	[RD3/3A]	E of Milner Rd	20m	AS/NCB	6,600	NCA	24.4m (20m)	No	11,400	IB	25.2m (20m)	No	13,100	IB	25.2m (20m)	No
	[RD10]	S of Maida Vale Rd	20m	AS	4,000		24.4m (20m)	No	7,800		25.2m (20m)	No	9,300		25.2m (20m)	No
Milner Road	[RD2]	S of TOD Connector	20m	AS	4,100	NCA	24.4m	Yes	7,000	IB	25.2m	Yes	8,200	IB	25.2m	No
	[RD9]	N of Berkshire Rd	20m	AS	7,000	-	24.4m (20m)	No	11,500		25.2m (20m)	No	13,000		25.2m (20m)	No
	[RD15]	E of Milner Rd	n.a.	n.a.	1,500		<20m	Yes	5,200	NCA	24.4m	Yes	6,500	NCA	24.4m	No
TOD Connector	[RD14]	S of Enterprise Blvd	n.a.	n.a.	700	AS	<20m	Yes	2,000	AS	<20m (24.4m)	Yes	2,400	AS	<20m (24.4m)	No
	[RD16]	S of TOD Precinct	n.a.	n.a.	800		<20m	Yes	3,100	NCA	24.4m	Yes	4,600	NCA	24.4m	No
														_	PAGE	15

#### Table 18 - Timing of Upgrades - Road Network

KC00604.000 High Wycombe South

				LN		20	)31				2041				2050	
Road	BOQ	Section	RR Current	category Current	VPD	LN	RR	Land Acquisition	VPD	LN	RR	Land Acquisition	VPD	LN	RR	Land Acquisition
	[-]	W of Milner Rd	20m	AS	500	AS	<20m	No	1,400	AS	<20m	No	1,600	AS	<20m	No
Sultana Road West		E of Milner Rd	20m	AS	800	AS	<20m	No	1,600	AS	<20m	No	1,900	AS	<20m	No
	[KD20]	E of TOD Precinct	20m	AS	452	AS	<20m	No	1,300	AS	<20m	No	1,700	AS	<20m	No
Stewart Road	[RD17]	E of Milner Rd	20m	AS	800	AS	<20m	No	3,400	NCA	24.4m	Yes	4,800	NCA	24.4m	No
<b>D</b>	[RD12]	S of Maida Vale Rd	20m	AS	700	AS	<20m	No	4,400	NCA	24.4m	Yes	5,700	NCA	24.4m	No
naven Street	[RD13]	S of Milner Rd	n.a.	n.a.	1,100	AS	<20m	Yes	4,100	NCA	24.4m	Yes	6,000	NCA	24.4m	No
Enternaise Devloyerd	[RD11]	W of Maida Vale Rd	20m	AS	1,900	AS	<20m	No	3,500	NCA*	24.4m (20m)	No	3,700	NCA	24.4m (20m)	No
Emerprise Boulevaru		N of TOD Connector	20m	n.a	700	AS	<20m	No	1,700	NCA*	20m	No	2,000	NCA*	20m	No
Brand Road	[RD19]	N of TOD Connector	20m	AS	300	AS	<20m	No	1,400	AS	<20m	No	2,100	AS	20m	No
Brae Road [	[R18]	E of TOD Connector	20m	AS	500	AS	<20m	No	1,900	AS	<20m	No	2,600	NCB	19.4m	No
Newburn Road	[-]	N of Maida Vale Rd	25.5m	AS	4,200	NCA	24.4m	No	5,700	NCA	24.4m	No	6,600	NCA	24.4m	No

The anticipated traffic volumes indicate that Berkshire Road should be upgraded to an Integrator A configuration. Given that the Liveable Neighbourhoods guideline generally applies to the residential areas, the nominal cross-section should be modified to cater for industrial traffic. On-street parking is not deemed appropriate on Berkshire Road west of Roe Highway, given this road will carry RAV vehicles. Further to this, a generously sized shared path is a safer cycling option than on-road cycle paths, given the quantum of RAV vehicles and the possible presence of Over-Size Over Mass vehicles on this route. Therefore, we believe that a road reservation of 25m is appropriate for this section of Berkshire Road.

Dundas Road is servicing an industrial area for most of its length; therefore, an adjusted Integrator B cross-section is suggested.

Milner Road and Maida Vale Road require Integrator B as an ultimate configuration. Although the interim Neighbourhood Connector A configuration will suffice, it is recommended that both roads are upgraded to the ultimate configuration when traffic volumes meet warrants. These two configurations have only minor differences; however, reconstruction of the road will cause unnecessary disturbance and cost.

TOD Connector is a new local distributor servicing the High Wycombe South Project Area. The ultimate configuration for this road is Neighbourhood Connector A; therefore, the land for the ultimate road configuration will be acquired initially.

Enterprise Boulevard is under construction as a part of Railway Station works. It will be constructed to a Neighbourhood Connector A standard. Actual future traffic counts on this road will depend on the design of the access points for commercial and community facilities in TOD Precinct.

Brand Road will be upgraded by 2041 to an urban standard, although its formal classification will not change (Access Street). This upgrade is directly related to the construction of the Primary School and District Open Space and is likely to occur concurrently to construction of these two community facilities.

Portions of existing roads (Brae Road and Brand Road west of TOD Connector and Sultana Road West south of Brand Road) will become subdivisional roads, and the responsibility for upgrade will be with a developer.

KC00604.000 High Wycombe South

## 5.2 Intersection Configuration

The table below outlines the requirement for upgrades on some of the key intersections on the network. The table below shows starting and the ultimate configuration of the intersection, expected contribution per precinct, the timing of the upgrade and whether the land acquisition is necessary. The current size of the road reservation was sourced from Nearmap in July 2021. The requirement for land acquisition was assessed for intersections independently of the adjoining road link; therefore, it reflects

the requirement for the land acquisition in addition to land acquisition for the widening of road links. The impact of each precinct was assessed for AM and PM peaks independently. The values below reflect the average impact of both peak times. Details of modelling, conclusions and apportionment are provided in Appendix 4 of this report. The reference in the brackets pertains to the infrastructure element in the associated Bill of Quantities.

#### Table 19 - Timing of Upgrades - Intersections

Intersection	BOQ	Starting Configuration	Ultimate Configuration	Residential Precinct %	TOD Precin %
M01. Roe Highway / Maida Vale Road	[INT02]	Half interchange	Half Interchange	18.85%	14.36%
M02. Maida Vale Road / Milner Road	[INT01]	T-intersection full movement	Roundabout	33.35%	23.20%
M03. Milner Road / Stewart Road	[INT18]	T-intersection full movement	Roundabout	64.72%	14.74%
M04. Milner Road / Raven Street	[INT17]	T-intersection full movement	Roundabout	61.43%	17.89%
M05. Milner Road / TOD Connector	[INT05]	The intersection doesn't exist	Signals	41.24%	16.36%
M06. Milner Road / Berkshire Road / Dundas Road	[INT15]	T-intersection full movement	Roundabout	17.23%	7.70%
M07. Berkshire Road / Roe Highway	[-]	Grade separated interchange	Grade separated interchange	2.00%	1.20%
M08. TOD Connector / Brand Road	[INT16]	The intersection doesn't exist	Four-way, sign controlled	100.00%	0.00%
M09. TOD Connector / Brae Road / Raven Street	[INT14]	The intersection doesn't exist	Full movement 4-way intersection	100.00%	0.00%
M10. Brae Road / Stewart Road	[INT09]	T-intersection full movement	T-intersection full movement	100.00%	0.00%
M11 Milper Deed / Sultana Deed Weet		Two staggered T-intersections	Section east of Milner Rd to be converted to a LILORI	54.60%	11.53%
WITT. WIINER NOAU / SUITAITA NOAU WEST		- full movement	Section west of Milner Rd to be converted to Cul-de-Sac	0.00%	100.00%
M12. Maida Vale Road / Dundas Road / Parking Access	[INT14]	Roundabout	Roundabout	21.87%	8.75%
M13. Maida Vale Road / Enterprise Boulevard*	[INT12]	T-intersection full movement	T-intersection full movement	36.91%	17.55%
M14. Maida Vale Road / Raven Street	[INT13]	The intersection doesn't exist	T-intersection full movement	37.82%	19.60%
M15. (old Dundas Road) / Dundas Road	[INT06]	T-intersection full movement	Signals	16.46%	7.85%
M16. Maida Vale Road / Newburn Road	[INT03]	T-intersection full movement	Roundabout	37.72%	22.47%
M17. Maida Vale Road / Butcher Road	[-]	T-intersection full movement	T-intersection full movement	0.63%	20.91%
M18. Maida Vale Road / Plover Road	[-]	T-intersection full movement	T-intersection full movement	37.13%	26.04%
M19. Maida Vale Road / Littlefield Road	[-]	T-intersection full movement	T-intersection full movement	36.52%	25.62%
M20. Milner Road / Nardine Close	[INT08]	T-intersection	Left in Left Out Right In	41.57%	11.73%
M21. Berkshire Road / Bonser Road	[-]	T-intersection full movement	Left In Left Out	15.80%	8.50%
M22. Berkshire Road / Ashby Close	[-]	T-intersection full movement	Left In Left Out	13.33%	8.10%
M23. Berkshire Road / Walters Way	[-]	T-intersection full movement	Left In Left Out	14.78%	8.44%
M24. Berkshire Road / Harrison Road	[-]	T-intersection full movement	Left In Left Out	13.65%	8.30%
M25. Dundas Road / Dundas Road (south)*	[-]	T-intersection full movement	T-intersection full movement	0.00%	2.32%

Year of Upgrade	Land Acquisition Required?
2031	No
2041	Yes
2031/2041	Yes
2041	No
2041	Yes
2041	Yes
2041	Yes
2041	No *
2041	No
2041	No
2041	Yes
2031	No
2041	Yes
2041	No
2041	No *
2041*	No
PAGE	17

KC00604.000 High Wycombe South

## 6 Impact on Cost Apportionment

#### 6.1 Basis of the Apportionment (State Planning Policy 3.6)

In April 2021 Department of Planning, Lands and Heritage adopted the revised State Planning Policy 3.6: Infrastructure Contributions. Section 6 of this document outlines the following fundamental principles for application:

a) <u>Need and the nexus</u>: The need for the infrastructure must be clearly demonstrated (need), and the connection between the development and the demand created should be clearly established (nexus).

b) <u>Transparency</u>: Both the method for calculating the infrastructure contribution and the manner in which it is applied should be clear, transparent, and simple to understand and administer.

c) <u>Equity:</u> Infrastructure contributions should be levied equitably from identified stakeholders within a contribution area, based on the relative contribution to need.

d) <u>Certainty:</u> The scope, timing, and priority for delivering infrastructure items, and the cost of infrastructure contributions and methods of accounting for escalation, should be clearly identified.

e) <u>Efficiency</u>: Contribution should be justified on a whole-of-life capital cost basis consistent with maintaining financial discipline on service providers by precluding the over-recovery of costs.

f) <u>Consistency</u>: The system for infrastructure contributions for apportioning, collecting and spending contributions should be consistent, efficient and transparent.

g) <u>Accountable</u>: That there is accountability in the manner in which infrastructure contributions are determined, collected and expended

h) <u>Right of consultation and review</u>: Landowners and developers have the right to be consulted on the manner in which development contributions are determined and the opportunity to seek a review by an independent third party regarding the calculation of costs, and return of funds.

This report considers the road infrastructure required to cater for the estimated vehicular volumes. Appropriate cycling and pedestrian infrastructure were considered in developing appropriate road cross-sections.

All of the infrastructure items discussed in this report can be considered "Development Infrastructure" as defined in Section 6.3, clause a) of SPP 3.6. and are listed as items 8-12 in Schedule 1 of the SPP 3.6.

Findings of this report will be utilised to apportion the construction cost of all movement infrastructure (inclusive of roads, intersections, cycling paths and shared paths).

Attachment 10.1.1.2

KC00604.000 High Wycombe South

## 6.2 Addressing Key Principles of SPP 3.6

The table below outlines how relevant SPP 3.6 principles were addressed in deriving cost apportionment for road infrastructure.

	Table 20 - Addressing	SPP 3.6 Principles
--	-----------------------	--------------------

Principles	Addressing the principle
a) <u>Need and the nexus</u>	A significant increase in population and commercial floor space will generate and attract high vehicular traffic. Current infrastructure may not have sufficied traffic without significant delays and/or safety risk; therefore, it is essential to determine where upgrades may be required to accommodate the increase establishing the need and nexus was set at 10% of traffic contribution; therefore, if a precinct contributes 10% or more of projected daily traffic in the ultim to trigger the requirement for cost apportionment. This threshold ensures that only the roads that are likely to have significant traffic increases due to the funded and apportioned according to traffic modelling, through the DCP. Conversely, roads and intersections in the broader network that are likely to experiand that are unlikely to require upgrades are not a DCP item. Extensive network and intersection modelling clearly delineated where the introduction of the new infrastructure or upgrade of the existing infrastructur within the Residential and Transit-Oriented Development Precincts. The proportion of passing traffic, traffic not originating or terminating in the High Wy separated to apportion costs in the DCP.
b) <u>Transparency</u>	<ul> <li>While the method of modelling and apportionment was quite complex, the basic principles will be set out in this report in a straightforward and easy-to-fol so the volume of traffic generated or attracted by each precinct is clearly identifiable on every intersection and road link. Passing traffic is also identified, a of this traffic component cannot be attributed to the DCP. Traffic associated with the High Wycombe Railway Station, originating outside of the High Wycom "passing traffic" in this assessment, as the road network surrounding the station will be constructed to cater for the traffic attracted by the railway station.</li> <li>Passing traffic – traffic not originating nor terminating in the High Wycombe South Project Area. <i>Example One:</i> Resident of High Wycombe (Not Industrial Area via Maida Vale Road, Milner Road or Dundas Road. <i>Example Two:</i> Resident of Forrestfield accessing Railway Station via Berkshire F</li> <li>Reciprocal traffic / reciprocity in traffic generation and attraction – traffic originating in one precinct. <i>Example Two:</i> Residents of the Residential Precinct travelling for shopping or recreation to TOD Precinct. <i>Example Two:</i> Residents of TOD Precinct. School in the Residential Precinct.</li> </ul>
<b>c) <u>Equity</u></b> (Continued on the following page)	<ul> <li>The cost for the infrastructure will be apportioned according to: <ul> <li>the results of traffic modelling in the precinct,</li> <li>the need generated by the future development,</li> <li>the party benefiting from the infrastructure.</li> </ul> </li> <li>Two key categories have been adopted in this report for the purposes of apportionment within the High Wycombe South Project Area: TOD Precinct and some reciprocity in the traffic generation and attraction between two precincts, this portion of traffic is minor. Reciprocal traffic has been apportion infrastructure and the key beneficiary. For example, any reciprocal traffic modelled on the section of the TOD Connector located within the TOD Precinct will The basic principles of the apportionment can be summarised as follows: <ul> <li>If the precinct (TOD Precinct or Residential Precinct) contributes more than 10% of daily traffic on an intersection or a road section, the DCP con contributes less than 10% of daily traffic, it is not deemed sufficient to trigger the upgrade requirement; therefore, the contribution is not required <i>Example:</i> If in the ultimate scenario (horizon year 2050) 25% of the traffic on a road section or an intersection comes from the Residential Precinct. If approximately 35% of daily traffic on the same infrastructure element is attracted by TC the Residential Precinct), then 35% of the cost for the upgrade will be apportioned to the TOD Precinct, 40% of the cost for the upgrade cannot be attributed to DCP and this portion of cost will have to be fur mechanism.</li> </ul> </li> </ul>

ient capacity to service the increase in se in traffic. A minimum threshold for timate scenario, it is deemed sufficient this development will be a DCP item, perience only minor increases in traffic

ure is a consequence of development ycombe South Project Area, has been

bllow manner . The model was set up as the cost proportional to the impact ombe South Project Area, was deemed n. Key terminology:

lorth) travelling to work in Forrestfield Road > Milner Road > TOD Connector.

he High Wycombe South Project Area. inct taking their children to the primary

nd Residential Precinct. While there is oned according to the location of the rill be apportioned to the TOD Precinct.

# ntribution is required. If the precinct

*inct, then 25% of the cost for the TOD Precinct (and is not originating in this example is deemed passing traffic funded through an alternate* 

PAGE

KC00604.000 High Wycombe South

Principles	Addressing the principle
	- If a road or an intersection is deemed necessary for functioning of one of the Precincts, regardless of the presence of the other Precinct, the cos where the access is necessary.
	<b>Example One:</b> Raven Street between Milner Road and Brae Road. This road link provides Residential Precinct with an access to a higher order Road or Berkshire Road). While some of the residents of TOD Precinct may travel on this road, the road is required to service the Residential Precinct constructed. Therefore, the cost for construction should be allocated fully to the Residential Precinct.
	<b>Example Two:</b> TOD Connector between Milner Road and Enterprise Boulevard. While the residents of the Residential Precinct will likely travel on a and community services within the TOD Precinct, should the TOD Precinct not proceed the residents will travel elsewhere to access these set. Therefore, this section of TOD Connector is essential for future commercial and community services within the TOD Precinct for the travel and community services within the TOD Precinct of the travel and community services within the TOD Precinct for future commercial and community services within the TOD Precinct but is optional for the travel of the upgrade should be apportioned to the TOD Precinct fully.
	<b>Exception:</b> Raven Street between Milner Road and Maida Vale Road and Raven Street / Maida Vale Road intersection. The modelling showed Precinct are likely to use this link as a shortcut to access Maida Vale Road and Dundas Road northbound, not to access services in TOD Precinct; the precinct proportionally to the daily traffic contributed.
d) <u>Certainty</u>	It is envisaged that both precincts will be fully built out by 2050. Modelling was completed for 2031, 2041 and 2050+ horizon years to determine when infras Each of the horizon years is associated with the proportional build out of the Project Area, so 2031 corresponds with an approximate 15% build out, 2041 of 2050 corresponds with the completion of structure plans (100% buildout). Although general assumptions on the build-out rate are discussed in this report, on many factors (such as the general real estate market, the interest of developers in this particular area, other opportunities in the Perth Metro area etc.)
e) Efficiency	The proposed upgrades have been designed to accommodate increased traffic demand but also to provide an appropriate balance between vehicular traffic, p Furthermore, the proposed infrastructure upgrades seek to minimally disrupt existing residences and businesses as land acquisition requirements are mi the infrastructure elements are proposed to be modified compared to Liveable Neighbourhoods to be accommodated within the existing road reservation safety.
·,	The modelling shows that some road links may trigger iterative upgrades (Maida Vale Road, Berkshire Road, Milner Road). Iterative upgrades would ac disruption to the community may cause angst which could be avoided. Therefore, to minimise abortive road upgrades and costs. it is proposed to constru- is close to trigger, rather than iterative road upgrades every several years.
f) <u>Consistency</u>	The advice on potential upgrades predominantly relies on Liveable Neighbourhoods 2009. General recommendations by the guideline are, on occasion, lo site constraints and vehicular/pedestrian safety.
g) <u>Accountable</u>	These two principles pertain to the administration of the DCP, which is outside the scope of this report
h) <u>Right of consultation and review</u>	

## st will be apportioned to the Precinct

r network (Milner Road > Maida Vale recinct even if the TOD Precinct is not

this link to access future commercial ervices and will use other road links. the Residential Precinct, and the cost

that the residents of the Residential therefore, cost is apportioned to each

structure upgrades might be required. corresponds with 65% buildout while t, the actual build-out rate will depend

public transport, cycling and walking. inimised wherever possible. Some of n and/or for vehicular and pedestrian

dd unnecessary cost to DCP and the ruct the ultimate configuration once it

ocally modified to take into account

PAGE

KC00604.000 High Wycombe South

## 6.3 Key Network Links

The table below shows the summary of proposed upgrades and the contribution per precinct. For purposes of this report, traffic attracted by the railway station precinct was assessed as "passing traffic". For details, please refer the Appendix 3 of this report (Network Modelling Report).



/alters Wy-	Average
ilner Road	Berkshire Road
6.37%	15.96%
79%	8.62%



PAGE 22







PAGE









Road	Section [BOQ]	2050 Volumes <sub>(VPD)</sub>	Configuration	Contribution per Pi
oad West	TOD Connector – Milner Road [-]	<1,500	Kingunga usagu pang         Mung	100% TOD Precinct (this road is cons railway station works and is not likely
Sultana R	Milner Road – Edge of TOD Precinct & Edge of TOD Precinct – Cul-de-sac [RD20]	1,900	Algebra       Algebra         Algebra       Algebra	Milner Road – Edge of TOD Precinct:         TOD Total         12.98%         Residential Total         0.00%       10.00%       20.00%       30.00%       40.         It is expected that this road will be brought to an u progresses.         Edge of TOD Precinct – Cul-de-sac       100%

Attachment 10.1.1.2



istructed as a part of y to require an upgrade)



urban standard as the development

## **Residential Precinct**

PAGE 27



Attachment 10.1.1.2

PAGE



Precin	ct	
	64.	83%
40.00% nct was	50.00% 60. recalculate	00% 70.00% ad to exclude

PAGE

Road	Section [BOQ]	2050 Volumes <sub>(VPD)</sub>	Configuration	Contribution per Pre
d (former Ibis Place)	TOD Connector – Maida Vale Road (East of Maida Vale Road, abutting TEC) [RD11]	3,600	ruturun Zinia Kanaka Kana	100% TOD Precinct This road will be constructed mainly as works. Once community facility is in p be required on the south side of road
Enterprise Boulevard	TOD Connector – Maida Vale Road (North of TOD Connector, abutting Community Facility) [RD11]	2,000	August	

Attachment 10.1.1.2

## ecinct

s a part of railway station place, a shared path will reservation.

PAGE

Road	Section [BOQ]	2050 Volumes <sub>(VPD)</sub>	Configuration	Contribution per Pre
Road	TOD Connector – Brae Road [RD19]	2,000	kippining autralia prog right autrosoftia daya right autrosoftia right autrosoftia r	<b>100% Residential Precinct</b> This road is expected to be upgraded at the ti the district open space are constructed. Tw options for road configuration which would
Brand R	TOD Connector – Brae Road (Variation along the Primary School Site) [RD19]	2,000	Kipinong unorang Jipong Lingtong Jipong	options for road configuration which wou facilities. * <u>NOTE:</u> Section of Brand Road southwest of Street. As this road will become a standard s for upgrade (bringing the road up to an urba developer. This is not DCP item.

Attachment 10.1.1.2

## recinct

time when the primary school and wo cross-sections show possible I cater the best for the adjoining

TOD Connector will be an Access ubdivisional road, the responsibility n road standard) is directly with the

PAGE

## 6.4 Key Intersections

The table below shows the summary of proposed upgrades and the contribution per precinct. For details, please refer the Appendix 4 of this report (Intersection Modelling Report)









Intersection [BOQ]	Current Configuration	Upgrade Requirements (Ultimate Configuration)	Precinc
M05. Milner Road / TOD Connector [ INT 05]	Intersection doesn't exist at present. Possibly it might be constructed as a sign-controlled intersection initially.	N Contraction Cont	TOD % 16.36% RES % 0.00% 10.00% 20
M06. Milner Road / Berkshire Road / Dundas Road [ INT 15]		AN	TOD % 7.70% RES % 0.00% 5.00%
	T-intersection full movement	Roundabout	

## ts Contribution









PAGE



Attachment 10.1.1.2

## **Precincts Contribution**

100% Residential Precinct

100% Residential Precinct

PAGE



PAGE



















Intersection [BOQ]	Current Configuration	Upgrade Requirements (Ultimate Configuration)	Precincts
M24. Berkshire Road / Harrison Road [ - ]	Image: constraint of the sector of the sec	Image: second	TOD % RES % 0.00% 5.00%
M25. Dundas Road / Dundas Road (old alignment) [ - ]	Fintersection full movement	Image: state	This intersection is be the railway works. It w 2050, apart for adjust upgrade o



eing constructed as a part of vill not require an upgrade by stment to accommodate the of Dundas Road.





City of Kalamunda

# HIGH WYCOMBE SOUTH - TOD & RESIDENTIAL PRECINCTS MAIDA VALE ROAD TOD CONNECTOR BLVD RAVENSWOOD ROAD



# Plan of upgrades and apportionment - Roads



Maida Vale Road



RR widening Year of

required Upgrade



1.8m 2.9m 2.3m 3.0m 3.0m 2.3m 1.7m 3.0m 20.0m







INTERSECTIONS MAY REQUIRE KERB ADJUSTMENT ONCE ADJACENT ROADS ARE UPGRADED. INCLUDED IN DCP INTERSECTIONS REQUIRING UPGRADE AND INCLUDED IN DCP

INTERSECTIONS MAY REQUIRE UPGRADE OR ADJUSTMENT IN FUTURE. NOT INCLUDED IN DCP.

