

SUB-SOIL DRAINAGE DETAIL FOR PIPEWORK BEHIND KERB

SCALE 1:25

NOTES:


1. SUBSOIL DRAINAGE PIPES MUST COMPLY WITH AS2439-PART1, 1981 TYPE 2 RIGID OR SIMILAR COUNCIL APPROVED PIPES.
2. SUBSOIL DRAINAGE LINE SHALL BE LAID FROM UPSTREAM OBVERT TO DOWNSTREAM INVERT.
3. GEOFABRIC TO BE BIDIM A14 OR SIMILARLY APPROVED MATERIAL.
4. SUBSOIL PIPE WORK TO BE PLACED ON THE VERGE SIDE OF THE STORMWATER DRAINAGE (TYPICAL).
5. UPSTREAM END OF SUB-SOIL PIPE NOT CONNECTED TO LINER SHALL BE PROVIDED WITH SURFACE RISER AND CIRCULAR CONCRETE OR CLASS B DUCTILE IRON OR CAST IRON MAINTENANCE COVER.
6. ALL MEASUREMENTS IN MILLIMETERS UNLESS NOTED OTHERWISE.

STANDARD SUBSOIL DRAINAGE DETAIL

SCALE 1:25

SECTION B-B

SCALE 1:10



TITLE:

STANDARD SUBSOIL DRAINAGE



DRN: G LAWRENCE	DATE: 31/07/2006
APPROVED:	SCALE: AS SHOWN
INTI:	DWG NO: SHEET 3/30
DATE:	